

Radial Arm Saw Safety Exam

Directions: Fill in the blank spaces with the words from the word bank.

1. Always wear _____ fitting clothes.
2. When switching a blade, tighten the arbor nut using the _____ wrenches used in removing the blade.
3. Be sure to always _____ all clamps, guards, and locking handles.
4. When ripping, feed material from _____ end of anti-kickback device.
5. Never leave saw _____ outward on the arm.
6. Never make _____ while saw is running.
7. Never leave the _____ zone while saw is running.
8. Be sure blade is not warped, _____ or cracked.
9. Do not attempt to _____ the machine by forcing a piece of wood against the blade.
10. The teeth of the blade should be facing _____ from the operator.
11. Do not crosscut in _____ direction.
12. Always use the _____ blade for the specific cross or rip cut.
13. Always keep your fingers _____ inches away from the blade.
14. It is _____ safe to talk to the operator while the saw is in use.
15. Please be sure to get _____ from your instructor before making any changes to the machine.

| |
|-------------|
| Permission |
| Four |
| Opposite |
| Snug |
| Reverse |
| Proper |
| Safety |
| Same |
| Extended |
| Eight |
| Dull |
| Tighten |
| Away |
| Not |
| Six |
| Adjustments |
| Stop |